

IN THE CLAIMS

Please amend the claims as follows:

1. (Currently Amended) An infrared light source, comprising:

one or more combiners coupled to at least a first pump laser operable to generate a first pump signal and a second pump laser operable to generate a second pump signal, the one or more combiners operable to combine the first pump signal and the second pump signal into couple a first optical signal, the first pump signal comprising at least a first wavelength and the second pump signal comprising at least a second wavelength, wherein the first wavelength of the first pump signal is substantially different than the second wavelength of the second pump signal; and generated by the first pump laser and a second optical signal generated by the second pump laser to a gain fiber, the gain fiber comprising a first waveguide structure; and

a Raman-wavelength shifter coupled to the one or more combiners, gain fiber, the wavelength shifter comprising a first waveguide structure and a second waveguide structure, the Raman wavelength shifter operable to receive the first optical signal and to wavelength shift at least a portion of the first optical signal based at least in part on a Raman effect, wherein the wavelength shifter operates to wavelength shift at least the first wavelength to an intermediate optical wavelength in the first waveguide structure and to wavelength shift the intermediate optical wavelength to a longer optical wavelength in the second waveguide structure, at least a portion of the Raman wavelength shifter comprising an intermediate waveguide structure coupled to a second waveguide structure capable of wavelength shifting at least one wavelength of the first optical signal to an intermediate wavelength in the intermediate waveguide structure and then a longer signal wavelength in the second waveguide structure;

wherein at least a portion of the intermediate optical wavelength is greater than the first wavelength of the first optical signal and wherein at least a portion of the longer optical signal-wavelength is greater than the intermediate optical wavelength; and

wherein the first waveguide structure is substantially different than the second waveguide structure.

2. (Previously Presented) The infrared light source of Claim 1, wherein the first pump laser is selected from the group consisting of a continuous wave laser and a pulsed laser.

3. (Currently Amended) The infrared light source of Claim 1, wherein the first pump laser is selected from the group consisting of a solid state laser, a Nd:YAG laser, a Nd:YLF laser, laser diodes, a semiconductor laser, and a cladding pump fiber ~~laser~~.

4. (Canceled)

5. (Currently Amended) The infrared light source of Claim 1, wherein the second pump laser is selected from the group consisting of a solid state laser, a Nd:YAG laser, a Nd:YLF laser, laser diodes, a semiconductor laser, and a cladding pump fiber ~~laser~~.

6. (Previously Presented) The infrared light source of Claim 1, wherein the second pump laser comprises a plurality of laser diodes capable of generating a plurality of pump signals substantially centered on a selected wavelength.

7. (Currently Amended) The infrared light source of Claim 6, wherein the second pump laser further comprises a multiplexer capable of combining the plurality of pump signals into the second ~~optical~~ pump signal.

8. (Previously Presented) The infrared light source of Claim 7, wherein the multiplexer is selected from the group consisting of a wavelength division multiplexer, a polarization multiplexer, and a power combiner.

9. (Currently Amended) The infrared light source of Claim 1, wherein the second wavelength of the second pump signal is ~~optical signal comprises a selected wavelength~~ selected from the group consisting of 980 nm, 1310 nm, 1390 nm, 1400-1499 nm, and 1510 nm.

10. (Currently Amended) The infrared light source of Claim 1, wherein the longer optical ~~signal~~ wavelength comprises a pulsed optical signal having a pulse repetition rate in the range of two (2) hertz to one hundred (100) megahertz.

11. (Currently Amended) The infrared light source of Claim 1, wherein the longer optical ~~signal~~ wavelength comprises a pulsed optical signal having a pulse width in the range of two (2) nanoseconds to one hundred (100) milliseconds.

12. (Currently Amended) The infrared light source of Claim 1, wherein a variation of the first wavelength of the first pump ~~optical~~ signal causes a variation in ~~wavelength of the longer optical~~ wavelength ~~signal~~.

13. (Previously Presented) The infrared light source of Claim 1, wherein the one or more combiners are selected from the group consisting of a wavelength division multiplexer and a power coupler.

14. (Currently Amended) The infrared light source of Claim 1, wherein the first waveguide structure ~~gain-fiber~~ is selected from the group consisting of a dispersion compensating fiber, a dispersion shifted fiber, a single mode fiber, a chalcogenide fiber, and a fused silica optical fiber.

15. (Previously Presented) The infrared light source of Claim 1, wherein at least a portion of the first waveguide structure is selected from the group consisting of an optical fiber, a hollow tube waveguide, an air core waveguide, and a planar waveguide.

16. (Currently Amended) The infrared light source of Claim 1, wherein the first waveguide structure at least partially contributes to increasing an optical energy of at least a portion of the first optical signal and wherein the increased optical signal energy is communicated from the first waveguide structure at a selected wavelength.

17. (Previously Presented) The infrared light source of Claim 1, wherein at least a portion of the second waveguide structure is selected from the group consisting of an optical fiber, a hollow tube waveguide, an air core waveguide, and a planar waveguide.

18. (Canceled)

19. (Canceled)

20. (Currently Amended) The infrared light source of ~~Claim 18~~ Claim 1, wherein at least a portion of the second waveguide structure comprises an optical fiber, wherein the optical fiber is selected from the group consisting of a mid-infrared optical fiber, a chalcogenide fiber and a ZBLAN fiber.

21. (Currently Amended) The infrared light source of Claim 1, wherein at least a portion of the second waveguide structure is an optical waveguide comprising a material selected from the group consisting of ZBLAN, sulfide, selenide, and telluride, a ZBLAN waveguide, a sulfide waveguide, a selenide waveguide, and a telluride waveguide.

22. (Canceled)

23. (Currently Amended) The infrared light source of Claim 1, wherein the longer optical ~~signal~~ wavelength comprises a wavelength of approximately 1.7 microns or more.

24. (Currently Amended) The infrared light source of Claim 1, wherein the longer optical ~~signal~~ wavelength comprises a wavelength in the range of two (2) microns to ten (10) microns.

25. (Currently Amended) The infrared light source of Claim 1, wherein the longer optical ~~signal~~ wavelength comprises a wavelength in the range of five (5) microns to seven (7) microns.

26. (Currently Amended) The infrared light source of Claim 1, further comprising a wavelength separator coupled to the ~~Raman~~ wavelength shifter and capable of transmitting at least a portion of a selected wavelength from the ~~Raman~~ wavelength shifter.

27. (Previously Presented) The infrared light source of Claim 26, wherein the wavelength separator is selected from the group consisting of a demultiplexer, one or more partially transmissive gratings, one or more partially transmitting mirrors, one or more Fabry Perot filters and one or more dielectric gratings.

28. (Currently Amended) The infrared light source of Claim 1, further comprising at least a third waveguide structure coupled to the ~~Raman~~ wavelength shifter, wherein ~~the third waveguide structure comprises a coupling loss between the third waveguide structure and the wavelength shifter comprises~~ of no more than five (5) decibels.

29. (Currently Amended) A method of shifting an optical ~~signal~~ wavelength to a longer optical ~~signal~~ wavelength, comprising:

~~combining coupling~~ a first ~~optical pump~~ signal generated by a first pump laser and a second ~~optical pump~~ signal generated by a second pump laser ~~into a first optical signal, the first pump signal comprising at least a first wavelength and the second pump signal comprising at least a second wavelength, wherein the first wavelength of the first pump signal is substantially different than the second wavelength of the second pump signal; to a gain fiber, the gain fiber comprising a first waveguide structure; and~~

~~receiving the first optical signal at a wavelength shifter, the wavelength shifter comprising a first waveguide structure and a second waveguide structure, wherein the first waveguide structure is substantially different than the second waveguide structure;~~

~~shifting at least the first wavelength one wavelength of the first optical signal to an intermediate optical wavelength using an the first intermediate waveguide structure based at least in part on a Raman effect; coupled to the gain fiber;~~

~~shifting the intermediate optical wavelength to a longer optical signal wavelength using the second a second waveguide structure coupled to the intermediate waveguide structure; and~~

~~wherein at least a portion of the intermediate optical wavelength is greater than the first wavelength one wavelength of the first optical signal and wherein at least a portion of the longer optical signal wavelength is greater than the intermediate optical wavelength. wavelength;~~

30. (Original) The method of Claim 29, wherein the second pump laser comprises a plurality of laser diodes capable of generating a plurality of pump signals substantially centered on a selected wavelength.

31. (Currently Amended) The method of Claim 30, wherein the second pump laser further comprises a multiplexer capable of combining the plurality of pump signals into the second ~~optical pump~~ signal.

32. (Currently Amended) The method of Claim 29, wherein the second wavelength of the second pump signal is optical signal ~~comprises a selected wavelength~~ selected from the group consisting of 980 nm, 1310 nm, 1390 nm, 1400-1499 nm and 1510 nm.

33. (Canceled)

34. (Canceled)

35. (Canceled)

36. (Currently Amended) The method of Claim 29, wherein the first waveguide structure at least partially contributes to increasing an optical energy of at least a portion of the first optical signal and wherein the increased optical signal energy is communicated from the first waveguide structure at a selected wavelength.

37. (Currently Amended) The method of Claim 29, wherein the longer optical ~~signal~~ wavelength comprises a wavelength of approximately 1.7 microns or more.

38. (Currently Amended) The method of Claim 29, wherein the longer optical ~~signal~~ wavelength comprises a wavelength in the range of two (2) microns to ten (10) microns.

39. (Currently Amended) The method of Claim 29, further comprising transmitting at least a portion of a selected wavelength from the ~~Raman~~ wavelength shifter into a third waveguide structure.

40. (Canceled)

41. (Canceled)

42. (Canceled)

43. (Canceled)

44. (Canceled)

45. (Canceled)

46. (Canceled)

47. (Canceled)

48. (Canceled)

49. (Canceled)

50. (Canceled)

51. (Canceled)

52. (New) The method of Claim 29, wherein the first waveguide structure is selected from the group consisting of a dispersion compensating fiber, a dispersion shifted fiber, a single mode fiber, a chalcogenide fiber, and a fused silica optical fiber.

53. (New) The method of Claim 29, wherein the second waveguide structure is selected from the group consisting of a chalcogenide fiber and a ZBLAN fiber.

54. (New) The method of Claim 29, wherein at least a portion of the second waveguide structure is an optical waveguide comprising a material selected from the group consisting of ZBLAN, sulfide, selenide, and telluride.

55. (New) The infrared light source of Claim 1, wherein the longer optical wavelength is adapted for use in a diagnostic procedure to detect tissue abnormalities.

56. (New) The infrared light source of Claim 1, wherein the longer optical wavelength is further coupled to a medical device adapted for insertion into a patient's body through an orifice in the body.

57. (New) The infrared light source of Claim 1, wherein the longer optical wavelength is adapted for use to ablate tissue with reduced collateral damage.

58. (New) The infrared light source of Claim 1, wherein the longer optical wavelength is adapted for use in a differential spectroscopic measurement based at least in part on a comparison of measurements taken from different portions of a sample.

59. (New) The infrared light source of Claim 1, wherein the longer optical wavelength is adapted for use in a measurement based at least in part on a comparison of a plurality of wavelengths transmitted through a sample.

60. (New) The method of Claim 29, wherein the longer optical wavelength is adapted for use in a diagnostic procedure to detect tissue abnormalities.

61. (New) The method of Claim 29, wherein the longer optical wavelength is further coupled to a medical device adapted for insertion into a patient's body through an orifice in the body.

62. (New) The method of Claim 29, wherein the longer optical wavelength is adapted for use to ablate tissue with reduced collateral damage.

63. (New) The method of Claim 29 wherein the longer optical wavelength is adapted for use in a differential spectroscopic measurement based at least in part on a comparison of measurements taken from different portions of a sample.

64. (New) The method of Claim 29, wherein the longer optical wavelength is adapted for use in a measurement based at least in part on a comparison of a plurality of wavelengths transmitted through a sample.